



	<b>UN38.3 Lithium Battery Test Summary for Texas Instruments</b> <b>Incorporated for models TI-83 PREMIUM CE, TI-84PLCE-T, TI-84PLCE, TI-NSPIRE CX, TI-NSPIRE CX CAS, TI-NSPIRE CX II, TI-NSPIRE CX II CAS, TI-NSPIRE CX II-T, TI-NSPIRE CX II-T CAS</b>
<b>1</b>	<b>Battery Manufacturer</b>
	<i>Confidential and Proprietary Texas Instruments Incorporated</i>
<b>2</b>	<b>Product Manufacturer</b>
	<i>Texas Instruments Incorporated  12500 TI Blvd  Dallas, TX 75243  TEL: +1-972-995-2011 Website: education.ti.com Email: Louis.le@ti.com</i>
<b>3</b>	<b>UN38.3 Test Lab</b>
	<i>Samsung SDI Safety Center  467 Beonyeong-ro, Seobuk-gu, Cheonan-si  Chungcheongnam-do Korea  TEL: +82-41-560-3114 Website: www.samsungsdi.com Email:  asm7809@samsung.com</i>
<b>4</b>	<b>Test Report Number</b>
	<i>SDI-UN-161101-01</i>
<b>5</b>	<b>Date of Test Report</b>
	<i>2016.01.11</i>
<b>6</b>	<b>Description of Cell or Battery</b>
	<i>Type: Lithium Ion Battery  Mass: 24.5grams  Watt-hour Rating: 4.44Wh  Physical Description: Rechargeable Prismatic Battery Pack with dimensions  43x52.75mm <span style="float: right;">Models:</span>  3.7L1200SP, 3.7L1200SPA (3.7V 1200mAh)</i>
<b>7</b>	<b>UN38.3 Tests Performed and Successfully Passed</b>
	<i>T1 Altitude Simulation, T2 Thermal Test, T3 Vibration, T4 Shock, T5 External Short Circuit, T6 Crush/Impact, T7 Overcharge, and T8 Forced Discharge.</i>
<b>8</b>	<b>Assembled Battery Testing Requirements</b>
	<i>Not Applicable</i>
<b>9</b>	<b>Edition of UN Manual Tests and Criteria Used</b>
	<i>Rev. 6</i>
<b>10</b>	<b>Name and Title of Signatory</b>
	<div style="display: flex; justify-content: space-between; align-items: center;"> <div style="text-align: center;">   Louis Le  Product Stewardship Manager </div> <div style="text-align: center;">  </div> </div>